



Specifications 諸元表

	MGL RETRACTABLE STOCK	MGL CRANE STOCK	MGL L RETRACTABLE STOCK	MGL S RETRACTABLE STOCK
	ICS-190	ICS-191	ICS-192	ICS-193
Length 全長	630-725 mm	675-780 mm	725-825mm	630-725 mm
Barrel length 槍管長度	200 mm	200 mm	295 mm	200 mm
Muzzle velocity 初速	Velocity varies according to different gas pressure and grenade. 根據不同的氣體壓力和手榴彈，初速會有所不同。			
Weight 重量	2200 g	2200 g	2700 g	2400 g
Grenade capacity 裝彈量	6 rounds (發)			
Caliber 槍管口徑	40 mm			
Handguard material 護木材質	Engineering plastic (工業用強化塑料)		Full metal (金屬)	

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定，以上規格僅供一般標準使用。