

BLE-XAE CO2

Specifications 諸元表

	BLE-006-SB-C
Length 全長	184 mm
Barrel length 槍管長度	85 mm
Muzzle velocity 初速	100 m/s (328 FPS)
Weight 重量	670 g
Caliber 槍管口徑	6 mm
Mag. Capacity 彈匣容量	24 rounds (發)
Material 材質	Engineering plastic (工業用強化塑料)
Slide material 滑套材質	Aluminum (鋁合金)

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定。以上規格僅供一般標準使用。