

Specifications 諸元表

	CES SD5 FIXED STOCK	CES SD6 RETRACTABLE	CES A4 FIXED STOCK	CES A5 RETRACTABLE	
	ICS-01	ICS-02	ICS-03	ICS-04	
Length 全長	780 mm	600-741 mm	680 mm	500-640 mm	
Barrel length 內管長度	230 mm	230 mm	230 mm	230 mm	
Muzzle velocity 初速	120 m/s (394 FPS)				
Weight 重量	2240 g	2300 g	2300 g	2000 g	
Mag. Capacity 彈匣容量	300 rounds (發)				
Material 材質	Full metal (金屬)				
Motor axle 馬達	Long (長軸)				

NOTE:

- 1. The product specification is for reference ONLY and may be subject to change.
- 2. Battery, charger and BB's are not included.
- 3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries; For AEG below 350 FPS and which use Turbo 2000 \ Turbo 3000 \ EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
- 4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
- 5. For GBB produt, it is recommended to use 12KG Green Gas.
- 6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:

Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK

Below 100 m/s (328 FPS): Italy Below 95 m/s (312 FPS): Japan Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定,以上規格僅供一般標準使用。



Specifications 諸元表

	CES-P A5 TACTICAL RETRACTABLE STOCK	CES-P MS1 SFS STOCK		
	ICS-18	ICS-19		
Length 全長	500-650 mm	490-760 mm		
Barrel length 內管長度	230 mm	230 mm		
Muzzle velocity 初速	120 m/s (394 FPS)			
Weight 重量	2800 g	2800 g		
Mag. Capacity 彈匣容量	230 rounds (發)			
Material 材質	Full metal (金屬)			
Motor axle 馬達	Long (長軸)			

NOTE:

- 1. The product specification is for reference ONLY and may be subject to change.
- 2. Battery, charger and BB's are not included.
- 3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries; For AEG below 350 FPS and which use Turbo 2000 \ Turbo 3000 \ EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
- 4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
- 5. For GBB produt, it is recommended to use 12KG Green Gas.
- 6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:

Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK

Below 100 m/s (328 FPS): Italy Below 95 m/s (312 FPS): Japan Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定,以上規格僅供一般標準使用。



Specifications 諸元表

	CES A4 Tactical Flashlight Handguard Fixed Stock	CES A5 Tactical Flashlight Handguard Retractable Stock	
	ICS-111	ICS-112	
Length 全長	714 mm	534-674 mm	
Barrel length 內管長度	230 mm	230 mm	
Muzzle velocity 初速	120 m/s (394 FPS)		
Weight 重量	2120 g	2150 g	
Mag. Capacity 彈匣容量	230 rounds (發)		
Material 材質	Full metal (金屬)		
Motor axle 馬達	Long (長軸)		

NOTE:

- 1. The product specification is for reference ONLY and may be subject to change.
- 2. Battery, charger and BB's are not included.
- 3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries; For AEG below 350 FPS and which use Turbo 2000 \ Turbo 3000 \ EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
- 4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
- 5. For GBB produt, it is recommended to use 12KG Green Gas.
- 6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:

Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK

Below 100 m/s (328 FPS): Italy Below 95 m/s (312 FPS): Japan Below 45 m/s (148 FPS): Korea

備註

槍支內裝將依據各市場規定要求而作不同設定,以上規格僅供一般標準使用。