

CS4AI

Specifications 諸元表

| | CS4A1 RETRACTABLE STOCK | CS4A1 RETRACTABLE STOCK EBB | CS4A1 RETRACTABLE STOCK LIGHTWAY | CS4A1 FIXED STOCK LIGHTWAY |
|-----------------------|----------------------------------|-----------------------------------|--|----------------------------------|
| | ICS-20 IMT-020-1 IMC-020-1 | ICS-320 | ICS-41 | ICS-42 |
| Length 全長 | 778-873 mm | 778-873 mm | 778-873 mm | 875 mm |
| Barrel length 內管長度 | 375 mm | 375 mm | 375 mm | 375 mm |
| Muzzle velocity 初速 | 120 m/s (394 FPS) | | 100 m/s (328 FPS) | |
| Weight 重量 | 3000 g | 2900 g | 2500 g | 2700 g |
| Mag. Capacity 彈匣容量 | 450 rounds (發) | | 300 rounds (發) | |
| Material 材質 | Full metal (金屬) | | Engineering plastic (工業用強化塑料) | |
| Motor axle 馬達 | Long (長軸) | | Long (長軸) | |

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定。以上規格僅供一般標準使用。

CS4 R.A.S.

Specifications 諸元表

| | CS4A1 TUBULAR R.A.S.L | CS4A1 TUBULAR R.A.S.S | CS4A1 TUBULAR R.A.S.L EBB | CS4A1 TUBULAR R.A.S.S EBB |
|-----------------------|--------------------------|--------------------------|------------------------------|------------------------------|
| | ICS-220 | ICS-221 | ICS-322 | ICS-323 |
| Length 全長 | 778-873 mm | 778-873 mm | 778-873 mm | 778-873 mm |
| Barrel length 內管長度 | 375 mm | 375 mm | 375 mm | 375 mm |
| Muzzle velocity 初速 | 120 m/s (394 FPS) | | | |
| Weight 重量 | 2900 g | 2850 g | 3000 g | 2950 g |
| Mag. Capacity 彈匣容量 | 450 rounds (發) | | | |
| Material 材質 | Full metal (金屬) | | | |
| Motor axle 馬達 | Long (長軸) | | | |

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定。以上規格僅供一般標準使用。

CS4 R.I.S.

Specifications 諸元表

| | CS4 R.I.S. | CS4 R.I.S. EBB | CS4 R.I.S. COMMANDO LIGHTWAY |
|-----------------------|--------------------|----------------|----------------------------------|
| | ICS-127 | ICS-321 | ICS-47 IPT-047-1 |
| Length 全長 | 730-815 mm | 730-815 mm | 730-815 mm |
| Barrel length 內管長度 | 263 mm | 263 mm | 263 mm |
| Muzzle velocity 初速 | 120 m/s (394 FPS) | | 100 m/s (328 FPS) |
| Weight 重量 | 3000 g | 3250 g | 2500 g |
| Mag. Capacity 彈匣容量 | 450 rounds (發) | | 300 rounds (發) |
| Material 材質 | Full metal (金屬) | | Engineering plastic (工業用強化塑料) |
| Motor axle 馬達 | Long (長軸) | | |

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定。以上規格僅供一般標準使用。

CS16A3

Specifications 諸元表

| | CS16A3 | CS16A3 R.A.S. |
|-----------------------|--------------------|---------------|
| | ICS-24 | ICS-30 |
| Length 全長 | 1025 mm | 1025 mm |
| Barrel length 內管長度 | 515 mm | 515 mm |
| Muzzle velocity 初速 | 120 m/s (394 FPS) | |
| Weight 重量 | 3370 g | 3750 g |
| Mag. Capacity 彈匣容量 | 450 rounds (發) | |
| Material 材質 | Full metal (金屬) | |
| Motor axle 馬達 | Long (長軸) | |

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000 · Turbo 3000 · EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定 · 以上規格僅供一般標準使用 ·

CS4 COMMANDO

Specifications 諸元表

| | CS4 Commando Crane Stock |
|-----------------------|--------------------------|
| | ICS-126 |
| Length 全長 | 730-815 mm |
| Barrel length 內管長度 | 263 mm |
| Muzzle velocity 初速 | 120 m/s (394 FPS) |
| Weight 重量 | 2400 g |
| Mag. Capacity 彈匣容量 | 300 rounds (發) |
| Material 材質 | Full metal (金屬) |
| Motor axle 馬達 | Long (長軸) |

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定，以上規格僅供一般標準使用。

CS4/16 SERIES

Specifications 諸元表

| | CS4 CQB Short Fixed Stock | CS4 CQB Short Fixed Stock LIGHTWAY | CS16A3 Fixed Stock LIGHTWAY | CS4 R.I.S. Short Fixed Stock LIGHTWAY |
|-----------------------|------------------------------|--|-----------------------------------|---|
| | ICS-120 | ICS-46 | ICS-142 | ICS-147 |
| Length 全長 | 600 mm | 600 mm | 1025 mm | 683 mm |
| Barrel length 內管長度 | 185 mm | 185 mm | 515 mm | 263 mm |
| Muzzle velocity 初速 | 120 m/s (394 FPS) | 100 m/s (328 FPS) | | |
| Weight 重量 | 2200 g | 1700 g | 2770 g | 2550 g |
| Mag. Capacity 彈匣容量 | 300 rounds (發) | | | |
| Material 材質 | Full metal (金屬) | Engineering plastic (工業用強化塑料) | | |
| Motor axle 馬達 | Long (長軸) | | Long (長軸) | |

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定・以上規格僅供一般標準使用・

CS4/16 SERIES

Specifications 諸元表

| | CS4 R.I.S. | CS4 S.I.R | CS4A1 LIGHTWAY |
|-----------------------|--------------------|----------------------------------|-------------------|
| | IMT-127-1 | ICS-48 | IPT-041-1 |
| Length 全長 | 730-815 mm | 825-910 mm | 778-873 mm |
| Barrel length 內管長度 | 263 mm | 375 mm | 375 mm |
| Muzzle velocity 初速 | 120 m/s (394 FPS) | 100 m/s (328 FPS) | |
| Weight 重量 | 3000 g | 3100 g | 2500 g |
| Mag. Capacity 彈匣容量 | 300 rounds (發) | | |
| Material 材質 | Full metal (金屬) | Engineering plastic (工業用強化塑料) | |

| | |
|------------------|--------------|
| Motor axle 馬達 | Long (長軸) |
|------------------|--------------|

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定。以上規格僅供一般標準使用。