

SG 551/552

Specifications 諸元表

	H51 LB MRS Folding Stock	H52 Commando Folding Stock	H52 Commando DE Folding Stock-TAN (Lightway)
	ICS-151	ICS-52	ICS-254
Length 全長	698-928 mm	470-728 mm	470-728 mm
Barrel length 內管長度	458 mm	263 mm	263 mm
Muzzle velocity 初速	120 m/s (394 FPS)		100 m/s (328 FPS)
Weight 重量	3000 g	2600 g	2100 g
Mag. Capacity 彈匣容量	400 rounds (發)		
Material 材質	Full metal (金屬)		Engineering plastic (工業用強化塑料)
Motor axle 馬達	Medium (中軸)		

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定。以上規格僅供一般標準使用。