

# CXP-UK1 CAPTAIN

## Specifications 諸元表

	CXP-UK1 CAPTAIN MTR	CXP-UK1 CAPTAIN
	ICS-262 IMT-262-1	ICS-263 IMT-263-1
Length 全長	617-693 mm	512 mm
Barrel length 內管長度	186 mm	186 mm
Muzzle velocity 初速	120 m/s (394 FPS)	
Weight 重量	2920 g	2630 g
Mag. Capacity 彈匣容量	300 rounds (發)	
Material 材質	Full metal (金屬)	
Motor axle 馬達	Long (長軸)	

### NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;  
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:  
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK  
Below 100 m/s (328 FPS): Italy  
Below 95 m/s (312 FPS): Japan  
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定，以上規格僅供一般標準使用。

# CXP-UK1

## Specifications 諸元表

	CXP-UK1	CXP-UK1 COMBINATION GEARBOX	CXP-UK1 R	CXP-UK1 R SR
	ICS-264 IMT-264-1	ICS-264C IMT-264C-1	ICS-265 IMT-265-1	ICS-267
Length 全長	700-795 mm	700-795 mm	811-906 mm	895-925 mm
Barrel length 內管長度	261 mm	263 mm	372 mm	375 mm
Muzzle velocity 初速	120 m/s (394 FPS)			
Weight 重量	2700 g	2587 g	2920 g	3380 g
Mag. Capacity 彈匣容量	300 rounds (發)			
Material 材質	Full metal (金屬)			
Motor axle 馬達	Long (長軸)			

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;  
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:  
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK  
Below 100 m/s (328 FPS): Italy  
Below 95 m/s (312 FPS): Japan  
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定。以上規格僅供一般標準使用。