

CXP-HOG FRONT WIRED

Specifications 諸元表

	CXP-HOG MTR STOCK FRONT WIRED	CXP-HOG CAPTAIN MTR STOCK	CXP-HOG QRS STOCK FRONT WIRED
	ICS-270 IMT-270-1	IMD-273-1	ICS-272 IMT-272-1
Length 全長	700-795 mm	617-693 mm	675-775 mm
Barrel length 內管長度	263 mm	186 mm	263 mm
Muzzle velocity 初速	120 m/s (394 FPS)		
Weight 重量	3000 g	2840 g	3000 g
Mag. Capacity 彈匣容量	300 rounds (發)		
Material 材質	Full metal (金屬)		
Motor axle 馬達	Long (長軸)		

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定，以上規格僅供一般標準使用。

CXP-HOG REAR WIRED

Specifications 諸元表

	CXP-HOG MTR STOCK REAR WIRED	CXP-HOG TUBULAR SR	CXP-HOG TUBULAR L SR
	ICS-271 IMT-271-1	ICS-274	ICS-275
Length 全長	700-795 mm	880-910 mm	895-925 mm
Barrel length 內管長度	263 mm	375 mm	375 mm
Muzzle velocity 初速	120 m/s (394 FPS)		
Weight 重量	3000 g	3300 g	3300 g
Mag. Capacity 彈匣容量	300 rounds (發)		
Material 材質	Full metal (金屬)		
Motor axle 馬達	Long (長軸)		

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000 · Turbo 3000 · EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定 · 以上規格僅供一般標準使用 ·

CXP-HOG TUBULAR SD

Specifications 諸元表

	CXP-HOG TUBULAR SD MTR	CXP-HOG TUBULAR SD S1	CXP-HOG TUBULAR SD SR	CXP-HOG TUBULAR SSD MTR
	ICS-380	ICS-381	ICS-382	ICS-383
Length 全長	800-880 mm	803-898 mm	880-910 mm	720-800 mm
Barrel length 內管長度	375 mm	375 mm	375 mm	303 mm
Muzzle velocity 初速	120 m/s (394 FPS)			
Weight 重量	2860 g	2920 g	3300 g	2960 g
Mag. Capacity 彈匣容量	300 rounds (發)			
Material 材質	Full metal (金屬)			
Motor axle 馬達	Long (長軸)			

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000 · Turbo 3000 · EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定 · 以上規格僅供一般標準使用 ·