

# CXP-16

## Specifications 諸元表

|                       | CXP-16 L             | CXP-16 S             |
|-----------------------|----------------------|----------------------|
|                       | ICS-238<br>IMT-238-1 | ICS-236<br>IMT-236-1 |
| Length<br>全長          | 885-980 mm           | 650-745 mm           |
| Barrel length<br>內管長度 | 303 mm               | 215mm                |
| Muzzle velocity<br>初速 | 120 m/s (394 FPS)    |                      |
| Weight<br>重量          | 3300 g               | 2600 g               |
| Mag. Capacity<br>彈匣容量 | 300 rounds (發)       |                      |
| Material<br>材質        | Full metal<br>(金屬)   |                      |
| Motor axle<br>馬達      | Long<br>(長軸)         |                      |

### NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;  
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:  
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK  
Below 100 m/s (328 FPS): Italy  
Below 95 m/s (312 FPS): Japan  
Below 45 m/s (148 FPS): Korea

### 備註:

槍支內裝將依據各市場規定要求而作不同設定。以上規格僅供一般標準使用。

# CXP-16

## Specifications 諸元表

|                       | CXP-16 L<br>Lightway             | CXP-16 S<br>Lightway |
|-----------------------|----------------------------------|----------------------|
|                       | ICS-239<br>IPT-239-1             | ICS-237<br>IPT-237-1 |
| Length<br>全長          | 730-825 mm                       | 650-745 mm           |
| Barrel length<br>內管長度 | 303 mm                           | 215 mm               |
| Muzzle velocity<br>初速 | 100 m/s (328 FPS)                |                      |
| Weight<br>重量          | 3000 g                           | 2300 g               |
| Mag. Capacity<br>彈匣容量 | 300 rounds (發)                   |                      |
| Material<br>材質        | Engineering plastic<br>(工業用強化塑料) |                      |
| Motor axle<br>馬達      | Long<br>(長軸)                     |                      |

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;  
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:  
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK  
Below 100 m/s (328 FPS): Italy  
Below 95 m/s (312 FPS): Japan  
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定。以上規格僅供一般標準使用。