

CXP-MMR

Specifications 諸元表

| | CXP-MMR DMR | CXP-MMR Carbine | CXP-MMR SBR |
|-----------------------|----------------------|----------------------|----------------------|
| | ICS-400 IMT-400-1 | ICS-401 IMT-401-1 | ICS-402 IMT-402-1 |
| Length 全長 | 975-1005 mm | 835-930 mm | 725-800 mm |
| Barrel length 內管長度 | 458 mm | 375 mm | 263 mm |
| Muzzle velocity 初速 | 120 m/s (394 FPS) | | |
| Weight 重量 | 3393 g | 2886 g | 2678 g |
| Mag. Capacity 彈匣容量 | 300 rounds (發) | | |
| Material 材質 | Full metal (金屬) | | |
| Motor axle 馬達 | Long (長軸) | | |

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定，以上規格僅供一般標準使用。