

CS4AI

Specifications 諸元表

	CS4A1 RETRACTABLE STOCK	CS4A1 RETRACTABLE STOCK EBB	CS4A1 RETRACTABLE STOCK LIGHTWAY	CS4A1 FIXED STOCK LIGHTWAY
	ICS-20 IMT-020-1 IMC-020-1	ICS-320	ICS-41 IPT-041-1	ICS-42
Length 全長	778-873 mm	778-873 mm	778-873 mm	875 mm
Barrel length 內管長度	375 mm	375 mm	375 mm	375 mm
Muzzle velocity 初速	120 m/s (394 FPS)		100 m/s (328 FPS)	
Weight 重量	3000 g	2900 g	2500 g	2700 g
Mag. Capacity 彈匣容量	450 rounds (發)		300 rounds (發)	
Material 材質	Full metal (金屬)		Engineering plastic (工業用強化塑料)	
Motor axle 馬達	Long (長軸)		Long (長軸)	

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定。以上規格僅供一般標準使用。

CS4 R.A.S.

Specifications 諸元表

	CS4A1 TUBULAR R.A.S.L	CS4A1 TUBULAR R.A.S.S	CS4A1 TUBULAR R.A.S.L EBB	CS4A1 TUBULAR R.A.S.S EBB
	ICS-220	ICS-221	ICS-322	ICS-323
Length 全長	778-873 mm	778-873 mm	778-873 mm	778-873 mm
Barrel length 內管長度	375 mm	375 mm	375 mm	375 mm
Muzzle velocity 初速	120 m/s (394 FPS)			
Weight 重量	2900 g	2850 g	3000 g	2950 g
Mag. Capacity 彈匣容量	450 rounds (發)			
Material 材質	Full metal (金屬)			
Motor axle 馬達	Long (長軸)			

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定。以上規格僅供一般標準使用。

CS4 R.I.S.

Specifications 諸元表

	CS4 R.I.S.	CS4 R.I.S. EBB	CS4 R.I.S. COMMANDO LIGHTWAY
	ICS-127 IMT-127-1	ICS-321	ICS-47 IPT-047-1
Length 全長	730-815 mm	730-815 mm	730-815 mm
Barrel length 內管長度	263 mm	263 mm	263 mm
Muzzle velocity 初速	120 m/s (394 FPS)		100 m/s (328 FPS)
Weight 重量	3000 g	3250 g	2500 g
Mag. Capacity 彈匣容量	450 rounds (發)		300 rounds (發)
Material 材質	Full metal (金屬)		Engineering plastic (工業用強化塑料)
Motor axle 馬達	Long (長軸)		

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定・以上規格僅供一般標準使用。

CS16A3

Specifications 諸元表

	CS16A3	CS16A3 R.A.S.
	ICS-24	ICS-30
Length 全長	1025 mm	1025 mm
Barrel length 內管長度	515 mm	515 mm
Muzzle velocity 初速	120 m/s (394 FPS)	
Weight 重量	3370 g	3750 g
Mag. Capacity 彈匣容量	450 rounds (發)	
Material 材質	Full metal (金屬)	
Motor axle 馬達	Long (長軸)	

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000 · Turbo 3000 · EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定 · 以上規格僅供一般標準使用 ·

CS4 COMMANDO

Specifications 諸元表

	CS4 Commando Crane Stock
	ICS-126
Length 全長	730-815 mm
Barrel length 內管長度	263 mm
Muzzle velocity 初速	120 m/s (394 FPS)
Weight 重量	2400 g
Mag. Capacity 彈匣容量	300 rounds (發)
Material 材質	Full metal (金屬)
Motor axle 馬達	Long (長軸)

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:
槍支內裝將依據各市場規定要求而作不同設定，以上規格僅供一般標準使用。

CS4 SIR

Specifications 諸元表

	CS4 S.I.R. ICS-48
Length 全長	825-910 mm
Barrel length 內管長度	375 mm
Muzzle velocity 初速	100 m/s (328 FPS)
Weight 重量	3100 g
Mag. Capacity 彈匣容量	300 rounds (發)
Material 材質	Engineering plastic (工業用強化塑料)
Motor axle 馬達	Long (長軸)

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定・以上規格僅供一般標準使用・

CS4/16 SERIES

Specifications 諸元表

	CS4 CQB Short Fixed Stock	CS4 CQB Short Fixed Stock LIGHTWAY	CS16A3 Fixed Stock LIGHTWAY	CS4 R.I.S. Short Fixed Stock LIGHTWAY
	ICS-120	ICS-46	ICS-142	ICS-147
Length 全長	600 mm	600 mm	1025 mm	683 mm
Barrel length 內管長度	185 mm	185 mm	515 mm	263 mm
Muzzle velocity 初速	120 m/s (394 FPS)	100 m/s (328 FPS)		
Weight 重量	2200 g	1700 g	2770 g	2550 g
Mag. Capacity 彈匣容量	300 rounds (發)			
Material 材質	Full metal (金屬)	Engineering plastic (工業用強化塑料)		

Motor axle 馬達	Long (長軸)	Long (長軸)
------------------	--------------	--------------

NOTE:

1. The product specification is for reference ONLY and may be subject to change.
2. Battery, charger and BB's are not included.
3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
For AEG below 350 FPS and which use Turbo 2000、Turbo 3000、EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
5. For GBB product, it is recommended to use 12KG Green Gas.
6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:
Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK
Below 100 m/s (328 FPS): Italy
Below 95 m/s (312 FPS): Japan
Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定。以上規格僅供一般標準使用。