

Specifications 諸元表

	CXP-08 QRS STOCK LIGHTWAY	CXP-08 CRANE STOCK LIGHTWAY	CXP-08 QRS STOCK EBB	CXP-08 CRANE STOCK EBB
	ICS-160 IPT-160-1	ICS-144	ICS-324	ICS-325
Length 全長	595-695 mm	650-745 mm	595-695 mm	650-745 mm
Barrel length 內管長度	200 mm	200 mm	200 mm	200 mm
Muzzle velocity 初速	100 m/s (328 FPS)		120 m/s (394 FPS)	
Weight 重量	2150 g	2300 g	2900 g	2900 g
Mag. Capacity 彈匣容量	300 rounds (發)			
Material 材質	Engineering plastic (工業用強化塑料)		Full metal (金屬)	
Motor axle 馬達	Long (長軸)			

NOTE:

- 1. The product specification is for reference ONLY and may be subject to change.
- 2. Battery, charger and BB' s are not included.
- 3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries;
 For AEG below 350 FPS and which use Turbo 2000 \ Turbo 3000 \ EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
- 4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
- 5. For GBB produt, it is recommended to use 12KG Green Gas.
- 6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:

Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK

Below 100 m/s (328 FPS): Italy Below 95 m/s (312 FPS): Japan Below 45 m/s (148 FPS): Korea

備註:

槍支內裝將依據各市場規定要求而作不同設定,以上規格僅供一般標準使用。