

## Specifications 諸元表

	CXP-MARS KOMODO	CXP-MARS SBR	CXP-MARS CARBINE	CXP-MARS DMR		
	ICS-300 IMT-300-1 IMD-300-1	ICS-301 IMT-301-1 IMD-301-1	ICS-302 IMT-302-1 IMD-302-1	ICS-303 IMT-303-1 IMD-303-1		
Length 全長	840-935 mm	705-800 mm	810-905 mm	980-1010 mm		
Barrel length 內管長度	375 mm	263 mm	375 mm	458 mm		
Muzzle velocity 初速	120 m/s (394 FPS)					
Weight 重量	3160 g	2940 g	3040 g	3610 g		
Mag. Capacity 彈匣容量	300 rounds (發)					
Material 材質	Full metal (金屬)					
Motor axle 馬達	Long (長軸)					

### NOTE:

- 1. The product specification is for reference ONLY and may be subject to change.
- 2. Battery, charger and BB' s are not included.
- 3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries; For AEG below 350 FPS and which use Turbo 2000 \ Turbo 3000 \ EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
- 4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
- 5. For GBB produt, it is recommended to use 12KG Green Gas.
- 6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:

Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK

Below 100 m/s (328 FPS): Italy Below 95 m/s (312 FPS): Japan

Below 45 m/s (148 FPS): Korea

# CXP-MARS 555

### Specifications 諸元表

	CXP-MARS KOMODO SSS	CXP-MARS SBR SSS	CXP-MARS CARBINE SSS	CXP-MARS DMR SSS		
	ICS-300S3 IMT-300S3-1 IMD-300S3-1	ICS-301S3 IMT-301S3-1 IMD-301S3-1	ICS-302S3 IMT-302S3-1 IMD-302S3-1	ICS-303S3 IMT-303S3-1 IMD-303S3-1		
Length 全長	840-935 mm	705-800 mm	810-905 mm	980-1010 mm		
Barrel length 內管長度	375 mm	263 mm	375 mm	458 mm		
Muzzle velocity 初速	120 m/s (394 FPS)					
Weight 重量	3067 g	3145 g	3617 g	3145 g		
Mag. Capacity 彈匣容量	300 rounds (發)					
Material 材質	Full metal (金屬)					
Motor axle 馬達	Long (長軸)					

#### NOTE:

- 1. The product specification is for reference ONLY and may be subject to change.
- 2. Battery, charger and BB's are not included.
- 3. For AEG above 360 FPS, it is available to use 11.1V Li-Po or 9.6V Ni-Mh batteries; For AEG below 350 FPS and which use Turbo 2000 \ Turbo 3000 \ EVO 35000 motor, it is recommended to use only 7.4V Li-Po or 8.4V Ni-Mh batteries.(EVO 25000 Motor is NOT included)
- 4. For SSS product, it can use 11.1V Li-Po or 7.4V Li-Po batteries Only.
- 5. For GBB produt, it is recommended to use 12KG Green Gas.
- 6. Muzzle velocity is measured by 0.20g BB's, and is adjusted to comply with market regulation /requirements for specific countries as shown below:

Below 106 m/s (350 FPS): Belgium, France, Netherlands, Portugal, Spain, UK

Below 100 m/s (328 FPS): Italy Below 95 m/s (312 FPS): Japan Below 45 m/s (148 FPS): Korea

### 備註:

槍支內裝將依據各市場規定要求而作不同設定,以上規格僅供一般標準使用。